

# SolarPegaFL-S


TOPCON Light-weight Module 500-510W

**Light-weight | Anti-fire | Walkable | Crack-free**

**Class A Fire Rated**

Powered by **TSR-Armor™** Technology

**Quality Assurance**



## Light-weight

Weight only 6.7 kg/m<sup>2</sup>, about 50% of traditional panels



## Walkable

TSR-Armor™ Technology: Resistant to step-on and vibration without cell cracks and power losses.



## Class A Fire Rated

Fire-resistive backsheet & TSR-Armor™ enable industry's first Class A fire rated light-weight module



## Easy-to-install

Direct bonding with structural adhesive, improving efficiency by 50%.

**510W**

Max-power

**22.9%**

Efficiency

**0-+5W**


Power-tolerance

**≤1%**

First-year Degradation

**≤0.4%**

Annual Degradation from Year 2-30



### Electrical performance parameters (STC:AM1.5 1000W/m<sup>2</sup> 25°C test error ±3%;NMOT:800W/m<sup>2</sup> 20°C 1m/s) Power Tolerance:0-+5W

Module Type	ZKFN-G2-122B 500		ZKFN-G2-122B 505		ZKFN-G2-122B 510	
Test Conditions	STC	NMOT	STC	NMOT	STC	NMOT
Pmax [W]	500	385	505	388.8	510	392.7
Vmp [V]	33.76	27.00	33.85	27.08	33.91	27.13
Imp [A]	14.83	13.94	14.94	14.04	15.06	14.16
Voc [V]	39.72	32.17	39.87	32.29	40.03	32.42
Isc [A]	15.36	14.59	15.40	14.63	15.45	14.68

### Mechanical parameters

Cell Type	Topcon cell 182.3*105mm
Dimension	1961*1134*25.5mm
Glass	Single glass,1.1mm reinforced glass
Frame	High-strength glass-fiber resin composite
Weight	14.7kg
Output Line	4mm <sup>2</sup> ,wire length 400mm (customizable)
Connector	Staubli Electrical Connectors AG – MC4 EVO2 Series
Junction-box	3 IP68-rated junction box

### Temperature coefficient

Temperature-coefficient of PMPP	[%/°C]	-0.33
Temperature-coefficient of Voc	[%/°C]	-0.27
Temperature-coefficient of Isc	[%/°C]	+0.045
NOCT	[°C]	45±2

### Application parameters

Max. System Voltage	DC 1500V
Power Tolerance	0-+5W
Operating Temperature Range	-40°C-+85°C
Max. Series Fuse Rating	25A
Mechanical Load	Front 2400Pa,back 2400Pa
Wind Resistance Class	Lv.17
Hailstone Test	25mm hailstone at the speed of 23m/s

### Package

Transportation	Container size	Quantity (pcs)	Quantity (per pallet)
Container	40' HQ	720	40
Platform Trailer	13m	800	40
Platform Trailer	17.5m	1120	40



Shandong ZKFN Solar Technology Co., Ltd.

Tel.: +86 400 6768 100 Web.: [www.zkfn.com](http://www.zkfn.com)

Add.: Factory 1 of XinShenglin,LvHaiHui Intelligent Manufacturing Industrial Park, Jining Economic Development Zone,Jining,Shandong,China

\*NOTE: ZKFN Solar reserves right to update the specification without notice. Please always obtain the most recent version of the datasheet.

202605\_V6.2.1\_EN